



Admixture Series

BOND BUDDY 168

Homopolymer
Bonding Agent

Novel non-toxic homopolymer bonding agent to increase bond strength for all kinds of wall substrates and tiles.

Uses

- To increase bond strength for concrete, brick, AAC and plaster substrate.

Benefits

- Increase bond strength at the interface in between concrete and plaster
- Stable at exterior and high humidity area
- Low VOC
- Ready to use

Complied Standard

| EN 998 | EN 1015 | BS 4551 |

www.starkendrymix.com.my

Admixture Series

BOND BUDDY 168

**Homopolymer
Bonding Agent**



TECHNICAL PROPERTIES

| | |
|-------------------|----------------------------------|
| Adhesive Strength | > 1.2 N/mm² |
| Drying Time | 20 - 30 minutes |
| Open Time | 3 Days |
| Water Diffusion | Improved |
| Water Resistance | Good |

PHYSICAL FEATURES

| | |
|------------------|--------------------------------|
| Package | 20ℓ & 5ℓ |
| Colour | Violet |
| Specific Gravity | 1.01 kg/ℓ |
| Chemical | Homopolymer Resin |
| Consumption | 10 - 12 m²/ℓ |

APPLICATION

SUBSTRATE PREPARATION

- 1 Substrate should be free from mould oil, grease, loose particles and contamination of foreign materials.
- 2 Use high pressure water jet to clean the surface and allow the substrate to dry.

MATERIAL PREPARATION

- 1 Do not dilute Bond Buddy 168
- 2 Shake or stir before use
- 3 Apply by brush or roller to substrate or on tiles to fully cover the surface
- 4 Plastering can be applied after drying for 30 minutes
- 5 Surface is open for 3 days
- 6 Paint the surface again if the 3 days open time past

RECOMMENDATION

- 1 Substrate should be strong and sound
- 2 Do not apply on wet surface

STORAGE

Shelf life is 12 months if stored in dry and cool place. Avoid direct sunlight exposure.

Starken Drymix Solutions Sdn. Bhd. (916505-X)

A-1-3A, Pusat Perdagangan Kuchai,
No.2, Jalan 1/127, Off Jalan Kuchai Lama,
58200 Kuala Lumpur, Malaysia.

T: +603-7982 8066 F: +603-7983 8066