

STÄRKEN

**Drymix
Solutions**

TM



Tile Adhesive Series

FINE FILL 302

**NARROW TILE GAP
FILLING COMPOUND**

Coloured cementitious tile grout designed for filling tile joints, providing a durable and aesthetic finish

Uses

- Ideal for filling tile joints on walls and floors
- Internal and external tile grout

Benefits

- Decoration to tiling with different colours
- High abrasion resistance
- Low shrinkage to reduce crack
- Consistent colour

www.starkendrymix.com.my

Tile Adhesive Series

FINE FILL 302

**NARROW TILE GAP
FILLING COMPOUND**



PHYSICAL FEATURES

Package	25 kg
Water Demand	7.0 - 8.0 ℓ
Consumption	Approx. 1.45 kg/m ² /mm
Filler Size	< 0.3 mm
Application Gap Width	1 - 6 mm
Open Time	20 mins
Pot Life	Approx. 1 hour

Consumption of Tile Grout on a tiling area (in $\frac{\text{kg}}{\text{m}^2}$)

$$= \frac{\text{Tile Length} + \text{Tile Width}}{\text{Tile Length} \times \text{Tile Width}} \times \text{Tile Thickness} \times \text{Gap Width} \times \text{Consumption}$$



APPLICATION

SUBSTRATE PREPARATION

- 1 Tiling work should be finished at least 24 hours prior to Fine Fill 302 application
- 2 Ceramic tiles and mosaic tiles should be washed clean and free from glue, paper and any other contamination
- 3 Dampening of tile gap is recommended prior to the application in hot climate

APPLICATION PROCEDURE

- 1 Mix 1 bag of 25 kg **Fine Fill 302** with 7.0 - 8.0 litres of water using electrical mixer for at least 3 minutes until homogeneous mixture is achieved
- 2 Apply grout into the tile joints diagonally using sponge trowel and ensure the joints are fully compacted with grout material
- 3 Excess grout on the tiles should be wiped away by using damp sponge or damp cloth

Note:

1. Unsanded tile grout is recommended for grout joints $\leq 3\text{mm}$ wide
2. Sanded tile grout is recommended for grout joints between 3mm to 12mm wide

CURING

- 1 Natural air curing is sufficient

STORAGE

Shelf life is 6 months if stored in dry and cool place

HEALTH & SAFETY

- 1 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- 2 In case of contact with eyes or skin, rinse immediately with water and seek medical advice if needed.
- 3 For complete information about the safe use of our product, please refer to the latest version of Safety Data Sheet.

Disclaimer:

The information provided in this data sheet has been carefully compiled using the most current references available. However, no warranty, guarantee, or representation is made regarding its accuracy, reliability, or completeness. Users are responsible for evaluating the suitability and adequacy of this information for their specific needs. We shall not be held liable for any loss or damage arising from the use of this information. This data sheet is subject to change or modification without prior notice as part of our ongoing product development.

Starken Drymix Solutions Sdn. Bhd.
201001032580 (916505-X)

Menara Chin Hin
Level 22-23, 8th & Stellar,
No. 1, Jalan Naga Emas, Sri Petaling,
57000 Kuala Lumpur, Malaysia

T: +603-7982 8066

Ver 1.0